

INTRODUCING

G-Series P25 Voice Paging Solutions

G4 Industry First
P25 Voice Pager

Supports
P25 Trunking
P25 Conventional
Conventional

Available In
700-800MHz



G5 Industry First Dual Band
P25 Voice Pager

Supports
Analog 2-Tone
P25 Trunking
P25 Conventional
Conventional

Available In
UHF & 700-800MHz
VHF & 700-800MHz



Both Models Feature:

Up to 128 Channels
IP67 RATING Waterproof & Dustproof
Submersible up to 3ft for 30 Minutes
High Impact Resistant Color Screen
Rugged Housing
2 Year Standard Warranty/ 3 Year Addition Available

Custom Wav File Alerts
Out of Range Alert
Text Messaging/ Image Transfer
Bluetooth
32 Minutes Voice Storage
32 Minutes Voice Memo

www.UnicationUSA.com

www.Facebook.com/UnicationUSAInc



Key Features

G4 Model includes:

- Accommodates Multiple P25 Trunked and P25 Conventional Systems
- Supports the 800MHz Analog Frequencies
- Supports up to 256 Control Channels/per Trunked System
- Supports Full Spectrum Scan for P25 Trunked System
- Supports Multiple TGIDs for Monitoring and Alerting
- Supports Priority TGID Scan
- Supports Multiselect for Efficient Use of Traffic Channels
- Supports 2-Tone on 800MHz Analog Frequencies
- Allows for Customized Alerts using WAV/MP3 Files



G5 Model Has All of the Above Features Plus:

- Each Band Supports P25 Trunking, P25 Conventional, Conventional Channel Monitoring and 2-Tone Decoding
- Full 2-Tone Function Mode Support (Selective Call, Monitor, Scan Options)
- Supports Multiple 2-Tone Codes per Frequency
- Alerting Options based on a Selector Knob Setting

Models	Frequency Range
G4 P25 Voice Pager - 700-800MHz	763-776MHz, 851-870MHz
G5 Dual Band Voice Pager- VHF & 700-800MHz	136-174MHz/ 763-776MHz, 851-870MHz
G5 Dual Band Voice Pager- UHF & 700-800MHz	441-470MHz/ 763-776MHz, 851-870MHz

Both Models Feature:

- Up to 128 Channels*
- IP67 RATING Waterproof & Dustproof*
- Submersible up to 3ft for 30 Minutes*
- High Impact Resistant Color Screen*
- Rugged Housing*
- 2 Year Standard Warranty/ 3 Year Addition Available*

- Custom WAV File Alerts*
- Out of Range Alert*
- Text Messaging/Image Transfer*
- Bluetooth*
- 32 Minutes Voice Storage*
- 32 Minutes Voice Memo*

Technical Specifications

Sensitivity	-116dBm	Ingress Protection Rating	IP67- Waterproof/Dustproof
Sensitivity/12dB SINAD	6 uV/ M	UL	Class I, Div. II
Frequency Stability	+1ppm	FCC	FCC Part 15
Adjacent Channel Selectivity	>60dB	MIL-STD	810E, Proc1 for Driving Rain
Spurious	>70dB	Channel Spacing	25kHz / 12.5KHz/6.25KHz
Image Rejection	>70dB	Battery	Lithium Polymer
Audio Output Linear	>300mW	Weight (w/out Battery)	<220g
Audio Distortion	<2%	Size (mm)	102 x 61 x 31.5
Speech SPL (at 12 inches)	96dB +3dB/-2dB	Temperature Range	-20C ~ +40C
Alert SPL (at 12 inches)	96dB +3dB/-2dB		